

Applying filters

Each of the primitive vector graphic classes supports the `filters` property, an array of objects derived from one of the classes in the `spark.filters` package. The following filter classes are included in the Flex 4.5 SDK:

- `BevelFilter`
- `BlurFilter`
- `ColorMatrixFilter`
- `ConvolutionFilter`
- `DisplacementMapFilter`
- `DropShadowFilter`
- `GlowFilter`
- `GradientBevelFilter`
- `GradientFilter`
- `GradientGlowFilter`
- `ShaderFilter`

Each filter class supports a set of properties that modify its effect on the graphical element. For example, the following `Path` object adds two filters, a drop shadow, and a blur:

```

• <s:Path data="M 20 0
•     C 50 0 50 35 20 35
•     L 15 35 L 15 45
•     L 0 32 L 15 19
•     L 15 29 L 20 29
•     C 44 29 44 6 20 6">
• <s:stroke>
• <s:SolidColorStrokecolor="0x888888"/>
• </s:stroke>
• <s:fill>
• <s:LinearGradient rotation="90">
• <s:GradientEntrycolor="0x000000" alpha="0.8"/>
• <s:GradientEntrycolor="0xFFFFFFFF" alpha="0.8"/>
• </s:LinearGradient>
• </s:fill>
• <s:filters>
• <s:DropShadowFilter distance="20" color="#333333"/>
• <s:BlurFilter/>
• </s:filters>
• </s:Path>

```