

```

• package {
• import flash.display.MovieClip;
• public class helloClass extends MovieClip {
• public function helloClass() {
• //constructor code
• }
• }
• }

```

5. Remove the line that says `//constructor code` and replace it with: `trace("Hello, World");`
6. Save your Class file.

Return to the `helloWorld.fla` file and test the movie. The result should be the words "Hello, World" posted to the Output panel.

Classes provide you a way in which you can create public and private class elements. The difference between the two is related to how you use the data. For instance, a public property can be shared throughout your whole Flash movie. A private property can only be used within the class in which it is defined.

Using namespaces

Namespaces are ways in which you can define the visibility of properties you're creating. This is commonly used in XML when you're importing documents using a URI indicator.

The following example is built using a class called `NamespaceExample`. The role of this class is to pull in an XML document and step through the formatting of the code. Using namespace, you can instruct Flash where to find a definition of the document type you're using. In this case, an RSS formatted-document type.

1. Create a new ActionScript 3.0 movie. Create the class `NamespaceExample`.
2. Create a simple RSS formatted XML document. You can use the following formatted RSS document:

```

• <rdf:RDF
• xmlns:rdf="http://www.w3.org/1999/02/22-rdf-syntax-ns#"
• xmlns="http://purl.org/rss/1.0/"
• xmlns:dc="http://purl.org/dc/elements/1.1/"
• <channel rdf:about="http://www.xml.com/cs/xml/
• query/q/19">
• <title>This is an RSS feed</title>
• <link>http://www.bbc.co.uk/</link>
• <description>This is a test RSS document.
• </description>

```