

```

• <language>en-us</language>
• <items>
• <rdf:Seq>
• <rdf:lirrdf:resource="http://www.bbc.co.uk/">
• </rdf:Seq>
• </items>
• </channel>
• <item rdf:about="http://news.bbc.co.uk/">
• <title>BBC News Center</title>
• <link>http://news.bbc.co.uk</link>
• <description>Welcome to the BBC News Center</description>
• <dc:creator>BBC</dc:creator>
• <dc:date>2010-02-12</dc:date>
• </item>
• <item rdf:about="http://www.bbc.co.uk/radio">
• <title>BBC Radio Center</title>
• <link>http://www.bbc.co.uk/radio</link>
• <description>Welcome to the BBC Radio Center
• </description>
• <dc:creator>BBC</dc:creator>
• <dc:date>2010-02-12</dc:date>
• </item></rdf:RDF>

```

3. Open the NamespaceExample class. Start by defining the package with a public class called NamespaceExample that will extend the functionality of the Sprite object:

```

• package
• {
• import flash.display.Sprite;
• public class NamespaceExample extends Sprite

```

4. Insert the namespace reference that describes how to use RSSXML:

```

• {
• private var rss:Namespace = new Namespace("http://purl.org/
rss/1.0/");
• private var rdf:Namespace = new Namespace("http://www.
w3.org/1999/02/22-rdf-syntax-ns#");
• private var dc:Namespace = new Namespace("http://purl.org/dc/
elements/1.1/");
• public function NamespaceExample()

```

5. RSS has several standard XML types. You are going to extract the following: title, creator, date, link, and description. Each of these items will