

dynamic text:

- `private var myTextField:TextField;`
4. The following creates a basic string you can insert into your text field:
- `private var someText:String = "Hello world.";`
5. A private function is used to define the physical position of the text field on the screen. You first need to declare the text field as a new object; then you can use the X and Y properties to place the text on the screen:
- `private function configureText():void`
 - `{`
 - `myTextField = new TextField();`
 - `myTextField.y = 200;`
 - `myTextField.x = 100;`
6. A `TextFormat` object is used to format the visual properties of the text. For instance, the following `TextFormat` object sets the font to “_sans”, the colour black, and font size 15:
- `var format:TextFormat = new TextFormat();`
 - `format.font = "_sans";`
 - `format.color = 0x000000;`
 - `format.size = 15;`
 - `myTextField.defaultTextFormat = format;`
 - `addChild(myTextField);`
7. The final two public functions tie the text string to the new formatted text field:
- `public function text()`
 - `{`
 - `configureText();`
 - `setValueOfTextField(someText);`
 - `public function setValueOfTextField(str:String):void`
 - `{`
 - `myTextField.text = str;`
 - `}`
8. Test your movie and you will see that you have a text string added to your screen.
- So why would you go through the hard work of adding a scripted text field to the screen when you can do the same thing with the Flash text object with no scripting? The reason is that there may be times when you want to dynamically create text fields and the `TextField` object gives you this option.