

messages. The Debug view contains controls for stepping through code, terminating a debugging session, and resuming a debugging session. The Variables view displays the values of all pre-declared variables that are currently in scope while application execution is stopped on a breakpoint. The Breakpoints view enables you to manage your breakpoints. The Expressions view enables you to evaluate and inspect arbitrary ActionScript expressions while application execution is stopped on a breakpoint. The Network Monitor allows you to monitor and introspect remote service calls. The new Network Monitor view enables you to monitor HTTP traffic sent between the Flex application and an application server at runtime.

Generating Code

Flash Builder 4.5 includes many features that enable you to generate and modify your application code. Some of these features have been part of the product since version 2, while others are new to Flash Builder 4.5

Generating getter and setter methods

ActionScript 3 has always supported the use of getter and setter methods to provide access to a class's private properties, but previous versions of Flash Builder didn't do anything to help developers build the required code. Getter and setter method generation is a relatively new feature added to the Flash Builder. You can now declare a public property and then use Flash Builder to convert it to a private property, supported by the required methods.

1. Create a new ActionScript class.
 2. Declare a public property named `myVar` data typed as a `String`. The ActionScript class might start looking like this:
 - `package`
 - `{`
 - `public class MyClass`
 - `{`
 - `public var myVar:String;`
 - `}`
 - `}`
 3. Place the cursor anywhere in the variable name.
 4. Choose `Source > Generate Getter/Setter`. A dialog box appears that prompts you for options.
 5. Accept all the dialog box's default settings and click OK.
- The public property is renamed with an underscore prefix and changed