

previous section of this chapter and declares a number of Button objects laid out vertically and centered:

```

• <?xml version="1.0" encoding="utf-8"?>
• <s:Application xmlns:fx="http://ns.adobe.com/mxml/2009"
• xmlns:s="library://ns.adobe.com/flex/spark"
• skinClass="skins.CustomAppSkinComplete">
• <s:layout>
• <s:VerticalLayout paddingTop="20"
horizontalAlign="center"/>
• </s:layout>
• <s:Button label="Button 1"/>
• <s:Button label="Button 2"/>
• <s:Button label="Button 3"/>
• <s:Button label="Button 4"/>
• </s:Application>

```

2. View the application in Design mode.
3. Right-click the first button and select Create Skin
4. Set Package to skins.
5. Set Name to CustomButtonSkin.
6. Check the option to Remove ActionScript styling code.
7. Click Finish. The new custom skin should be created and opened in Design mode.
8. Click the Source button to look at the new skin component's code.

Assigning custom skins with CSS

As described in a previous section of this chapter, the skinClass attribute is an inline style declaration that styles only the current Button instance. If you want to style all instances of the Button class throughout the application, first remove the skinClass attribute from the MXML code you used to create the custom skin, and then declare skinClass in a style sheet that affects the entire application. Open AppWithButtons.mxml in Source mode and remove the skinClass attribute from the first Button object. Then add the following code above the first <s:Button> declaration:

```

• <fx:Style>
• @namespace s "library://ns.adobe.com/flex/spark";
• s|Button {
• skinClass: ClassReference("skins.CustomButtonSkin");
• }
• </fx:Style>

```