

at runtime is generated based on a model file in `html-template` named `index.template.html`. In addition, any files in the source-code root that aren't either code files built in MXML or ActionScript, or that don't represent embedded assets, such as binary graphical files, are copied, along with their directory structure, to the output folder as well.

The `html-template` directory contains three files and one subfolder:

- ▶ **index.template.html** - A model file that is the basis for the generated HTML “wrapper” files that call the application at runtime.
- ▶ **swfobject.js** - A JavaScript library containing functions used at runtime to load Flash Player. This file also contains “sniffer” code that can discover whether Flash Player is currently loaded on the user's desktop and, if so, which version.
- ▶ **playerProductInstall.swf** - A Flash application that's used to upgrade a user's system when Flash Player 6.65 or higher is installed.
- ▶ **The history subfolder.** Contains files to implement the history management feature (for non-IE browsers only):
 - `historyFrame.html` is a model for an HTML page that's loaded into an `<iframe>` in the main page at runtime.
 - `history.js` is a JavaScript library containing functions that are called by `historyFrame.html`.
 - `history.css` contains Cascading Style Sheet (CSS) rules to suppress the visibility of the history frame in the main page.

The HTML wrapper template

The HTML template file, `index.template.html`, contains a combination of HTML code, calls to JavaScript functions that are stored in `swfobject.js`, “History” files that manage the navigation history & deep linking and placeholders for values that are passed to the generated version of the file. At compile time, the HTML template is used to generate an HTML “wrapper” file that you deploy to your Web server.

The HTML `<head>` section

The `<head>` section of the model HTML file contains links to a set of CSS and JavaScript files. The `<title>` element contains a variable that's filled in from the Application's `pageTitle` property:

- `<title>${title}</title>`

To fill in this value in the generated HTML wrapper page, set the `pageTitle` property in the `<s:Application>` start tag: