

If you change the contents of `flex-config.xml`, you should “clean” all projects to force recompilation. Choose **Project > Clean**, select **Clean all projects**, and click **OK**. The rest of the script completes the version evaluation and runs the application:

```

• var xiSwfUrlStr = "playerProductInstall.swf";
• var flashvars = {};
• var params = {};
• params.quality = "high";
• params.bgcolor = "${bgcolor}";
• params.allowscriptaccess = "sameDomain";
• var attributes = {};
• attributes.id = "${application}";
• attributes.name = "${application}";
• attributes.align = "middle";
• swfobject.embedSWF(
• "${swf}.swf", "flashContent",
• "${width}", "${height}",
• swfVersionStr, xiSwfUrlStr,
• flashvars, params, attributes);
• <!-- JavaScript enabled so display the flashContent div in
case it is
• not replaced with a swf object. -->
• swfobject.createCSS("#flashContent",
"display:block;text-align:
• left;");

```

The call to `swfobject.embedSWF()` dynamically generates HTML code that runs Flash Player and the application at the location of the `<div>` with an id of `flashContent`. The call to `swfobject.createCSS()` hides the remainder of the `<div>` tag’s contents so doesn’t display if the application runs successfully. The `<head>` section contains the `<div>` tag with an id of `flashContent`:

```

• <div id="flashContent">
• <p>
• To view this page ensure that Adobe Flash Player version
${version _ major}.${version _ minor}.${version _ revision} or
greater is installed.
• </p>
• <a href="http://www.adobe.com/go/getflashplayer">
• <img src="http://www.adobe.com/images/shared/download_
buttons/get_flash_player.gif" alt="Get Adobe Flash Player"

```