

```

/>
• </a>
• </div>

```

Its contents are only displayed if the application or the Flash upgrade installer aren't loaded successfully. By default, it displays a text message indicating which version of Flash Player is required and a linked image that takes the user to the Adobe Web site to download the latest version of Flash Player. You can customize this section of the HTML code as desired.

Deploying the Application

You've created the application, and it runs beautifully in your development and testing environment. Now you want to share the application with your users. This section describes how to create a version of the application that's suitable for public release and make the application available to your audience.

Creating a release build

The version of the application that's created in your output folder, and that you run during the testing and debugging phase of development, is the "debug" version of the application. This compiled SWF file is significantly larger than the version you'll ultimately deploy for your users, because it contains additional internal information that's used only during debugging.

In Flex Builder 2, the debug and release builds of the application were placed in a single output folder. To deploy the application, you copied all files except the HTML and SWF files with the word debug in their filenames to the Web server. Starting with version 3, Flex Builder separates the debug and release builds into separate folders and requires a manual export process for the release build.

To create a release build of a Flex Web application, follow these steps:

1. From the Flash Builder menu, choose Project > Export Release Build, or File > Export > Release Build.
2. In the Export Release Build dialog box, make these choices:
 - a. Select the application you want to export.
 - b. Indicate whether you want to enable the View Source feature.
 - c. Select a folder to which you want to export the release build.
3. Click Finish to export the release build.

A release build folder contains only a single application and its supporting files. In contrast, the bin-debug folder contains the debug versions of all applications in a project. After exporting the release build, you should