

new browser window. The new window then has a fresh “history,” which means the browser’s Back button is disabled and the user can’t accidentally unload the application by trying to go back to a previous screen. The following HTML code would open the application from the home page of a web site

- `<a href="registration/registration.html" target="_blank"/>`

Integrating an application into an existing Web page

Some Flex applications are designed to be presented as applets (an application that represents only part of a Web page). This is easy to accomplish if you have some working knowledge of HTML.

1. Create a region of a Web page where you want to host the application. Design it just as you would to host an image, an ActiveX control, or a Java applet. You can use HTML tables or more modern `<div>` tags with CSS to control the size and position of the hosting region.
2. In the Flex application code, set the `<s:Application>` tag’s height and width to a specific number of pixels that will make the application size match the available space in the Web page. For example, if you have a `<div>` tag in the hosting page that’s 300 pixels high and 200 pixels wide, use this code in the Flex application to size it appropriately:

- `<s:Application xmlns:fx="http://ns.adobe.com/mxml/2009"`
- `xmlns:s="library://ns.adobe.com/flex/spark"`
- `xmlns:mx="library://ns.adobe.com/flex/mx"`
- `height=»300» width=»200»>`

When the application is compiled, the height and width settings are passed into the generated HTML file.

3. Copy the JavaScript includes and initialization code from the `<head>` section of the generated HTML wrapper file to the `<head>` section of the hosting HTML page.
4. Create a `<div>` element with an id of `flashContent` in your Web page where you want to display the application.

When you deploy a hosted Flex applet to a Web server, be sure to include all the same files as before: the JavaScript library, history files, and upgrade installer SWF file (`playerProductInstall.swf`). 