

textarea and button elements. It provides a declarative way to focus a form control during page load. Using this feature should enhance the user experience as the user can turn it off if the user does not like it, for instance.

- ▶ A new placeholder attribute can be specified on the input and textarea elements. It represents a hint intended to aid the user with data entry.
 - `<input type=email placeholder="a@b.com">`
- ▶ The new form attribute for input, output, select, textarea, button, label, object and fieldset elements allows for controls to be associated with a form. These elements can now be placed anywhere on a page, and still be associated with a form.
 - `<label>Email:`
 - `<input type=email form=foo name=email>`
 - `</label>`
 - `<form id=foo></form>`
- ▶ The new `<required>` attribute applies to input, select and textarea. It indicates that the user has to fill in a value in order to submit the form.
 - `<label>Color: <select name=color required>`
 - `<option value="">Choose one`
 - `<option>Red`
 - `<option>Green`
 - `<option>Blue`
 - `</select></label>`
- ▶ The input element has several new attributes to specify constraints: autocomplete, min, max, multiple, pattern and step.

Other attributes

- ▶ The script element has a new attribute called `async` that influences script loading and execution.
- ▶ The html element has a new attribute called `manifest` that points to an application cache manifest used in conjunction with the API for offline Web applications.
- ▶ The link element has a new attribute called `sizes`. It can be used in conjunction with the icon relationship (set through the `rel` attribute; can be used for e.g. favicons) to indicate the size of the referenced icon.
- ▶ The ol element has a new attribute called `reversed`. When present, it indicates that the list order is descending.
- ▶ The iframe element has three new attributes called `sandbox`, `seamless`,