

Fonts Module extends font support in CSS2.1 and redefines the behaviour of certain features at a time when the lack of an interoperable web font format frustrates many developers. Internet Explorer 9 provides full compliance with the CSS3 Fonts Module, including interoperable implementations of the `@font-face` rule, font-weight mapping, font-size mapping, and the font-stretch property. Internet Explorer 9 also adds support for the Web Open Font Format (WOFF), which repackages spline font (sfnt)-based font files (TrueType, OpenType, and Open Font Format fonts) by compressing each table individually using a ZIP compression format. Raw fonts (TrueType fonts with embedded permission bit that is not set) are also supported.

The font-weight property calculates font weights as specified in the CSS3 Fonts Module.

The font-size property build a scaling factor Also, keywords and HTML heading sizes are now mapped as specified in the CSS3 Fonts Module.

The font-stretch property selects a normal, condensed, or expanded face from a font family. This property is also available as a `@font-face` rule descriptor.

The `@font-face` Rule enables font linking. That is, a style sheet can reference a specific font file for the browser to download and use. For instance, consider the following markup.

```
• @font-face {
    font-family: MyFont;
    src: url(http://mysite/fonts/MyFont.ttf)
        format("embedded-opentype");
}
p {font-family: MyFont, serif;
}
```

In this example, the `@font-face` rule instructs the browser to go to the URL specified in the `src` descriptor to download the font file that contains the specified font.

The unicode-range descriptor, which enables you to specify the range of Unicode characters supported by a given font. For instance, the following code example specifies the range of basic ASCII characters.

```
• @font-face {
    font-family: MyFont;
    src: url(http://mysite/fonts/MyFont.ttf);
    unicode-range: U+0-7F;
```