

- ▶ deg: degrees (angle unit)
- ▶ grad: grads (angle unit)
- ▶ rad: radians (angle unit)
- ▶ turn: turns (angle unit)
- ▶ ms: milliseconds (time unit)
- ▶ s: seconds (time unit)
- ▶ rem: font size of the root element (relative length unit)
- ▶ vw: viewport width (relative length unit)
- ▶ vh: viewport height (relative length unit)
- ▶ vm: smaller of viewport width or height (relative length unit)
- ▶ ch: zero-width (width of the zero glyph in the rendering font; relative length unit)
- ▶ attr() function is used for generated content. It can be applied on any property and accept multiple arguments.
- ▶ calc(): calculates values using arithmetic operators and is usable wherever length values are allowed

CSS3 Selectors Module

The CSS3 Selectors Module specifies several additions to CSS selector syntax. They include structural pseudo-classes, the :target pseudo-class, UI element states pseudo-classes, the negation pseudo-class, and the UI element fragments pseudo-element.

Structural pseudo-classes enable selection based on extra information in the document tree that can't be selected using simple selectors or combinators.

The following selects an E element that is the root of the document.

E:root

The following selects an E element that is the n-th child of its parent.

E:nth-child(n)

The following selects an E element that is the n-th child of its parent, counting from the last one.

E:nth-last-child(n)

The following selects an E element that is the n-th sibling of its type.

E:nth-of-type(n)

The following selects an E element that is the n-th sibling of its type, counting from the last one.

E:nth-last-of-type(n)

The following selects an E element that is the last child of its parent.