

E:last-child

The following selects an E element that is the first sibling of its type.

E:first-of-type

The following selects an E element that is the last sibling of its type.

E:last-of-type

The following selects an E element that is the only child of its parent.

E:only-child

The following selects an E element that is the only sibling of its type.

E:only-of-type

The following selects an E element that has no children (including text nodes).

E:empty

The target pseudo-class selects the target element of the referring URI. A fragment identifier is used to identify a location within a page, and is formed using a number sign followed by an anchor identifier—for example, http://www.example.com/mypage.html#section_3.

The following selects the div element of class important that is the target element of the referring URI. If the document's URI has no fragment identifier, there is no target element.

div.important:target

The UI element states pseudo-classes are used to select UI elements (form controls such as radio buttons or check boxes) that are in a certain state—enabled, disabled, or selected (checked).

The following selects an E form control element that is enabled.

E:enabled

The following selects an E form control element that is disabled.

E:disabled

The following selects an E form control element that is selected.

E:checked

The :indeterminate pseudo-class selects radio buttons and check boxes whose toggle states cannot be determined—they are neither checked (selected) nor unchecked (cleared). The following selects an E form control element whose state cannot be determined.

E:indeterminate

Note The :indeterminate pseudo-class is no longer defined in the current CSS3 specification, but is supported in many popular browsers.

The negation pseudo-class takes a simple selector as an argument to select elements that are not selected by that argument. The following selects