

BROWSER SUPPORT FOR DIFFERENT CODECS			
Browser	Details	Video Codec	Audio Codec
Internet Explorer	Version 9.0 and later	MP4 container, H.264 video, WebM, Baseline, Main, and High profiles	MP3, and AAC in MP4 container
Mozilla Firefox	Version 3.5 and later	Theora Videos.	Vorbis audio in an Ogg container
Google Chrome	Version 3.0 and later	Theora Videos.	Vorbis audio in an Ogg container
Safari	Version 3.0 and later	H.264 video (main profile)	AAC audio in an MP4 container.
Opera	Version 10.5 and later	Theora Videos.	Vorbis audio in an Ogg container
iPhone	Version 3.0 and later	H.264 video (baseline profile)	AAC audio ("low complexity" profile) in an MP4 container.
Android	Version 2.0 and later	H.264 video (baseline profile)	AAC audio ("low complexity" profile) in an MP4 container.

plugins with high install rates, they are often blocked in controlled corporate environments. Some users choose to disable these plugins due to the ostentatious advertising. Then there is security issues associated with some of them. Also sometimes it is difficult for some plugins to integrate their displays with the rest of browser content - causing clipping or transparency issues.

The media elements expose a common, integrated, and scriptable API to the document. As a developer, your use of the new media elements allows very simple ways to script the control and playback of content. We will see multiple examples of this later in the chapter.

AUDIO

Let us first take a look at the Audio tag:

The Spec:

Currently, the HTML5 spec defines five attributes for the <audio> element:

1. **src** — a valid <abbr>URL</abbr> specifying the content source.
2. **autoplay** — a boolean specifying whether the file should play as soon as it can.
3. **loop** — a boolean specifying whether the file should be repeatedly played.
4. **controls** — a boolean specifying whether the browser should display its default media controls.
5. **preload** — none / metadata / auto — where 'metadata' means preload just the metadata and 'auto' leaves the browser to decide whether to preload the whole file.

Incidentally these attributes are also defined for the <video> element.

Let's create a simple example that will play an audio file: