

```
<audio src="SultansofSwing.ogg" controls preload="auto" autobuffer></audio>
```

To create your own controls, you can use the API methods defined by the spec:

- ▶ Load () - Loads the media file and prepares it for playback.
- ▶ play() — plays the audio
- ▶ pause() — pauses the audio
- ▶ canPlayType() — interrogates the browser to establish whether the given mime type can be played
- ▶ buffered() — attribute that specifies the start and end time of the buffered part of the file

The source

The best way to force the browsers into playing audio is to use the <source> element. The browser will try to load the first audio source, and if it fails or isn't supported, it will move on to the next audio source. In addition, we can embed a Flash player if all else fails:

```
• <audio controls preload="auto" autobuffer>
  <source src="elvis.mp3" />
  <source src="elvis.ogg" />
  <!-- now include flash fall back -->
</audio>
```

•

Cross-Browser Implementation

HTML5's <video>, <audio>, and <canvas> support fallback content. Meaning anywhere they are supported, they visually hide content placed beneath them. This allows you to target older browsers with a plug-in, or a link to alternate content. But as soon as a browser adds support for these elements, they automatically use them e.g.

```
• <!-- Elements with fallback content -->
• <audio id=vid1 controls width>
• <source src="audio.mp3" type="audio/mp3" />
• <source src="audio.ogg" type="audio/ogg" />
• <object type="application/x-silverlight-2"
  width="640" height="384">
•
• <a href="test.mp3">
•   Download Audio
• </a>
```