

The template contains the basic application functionality as well as the functionality for displaying the contents of a flash file on the device screen.

To use the Flash Based Application template, the `FLASH_SERVICE` and `SYSTEM_SERVICE` privileges are required. (The `SYSTEM_SERVICE` privilege is needed because the Flash Based Application template contains privileged methods by default.)

### ► **bada Empty Project**

This template is suitable for creating a project with project files only, without any source or include files. The template is used if you have existing source files that you want to import into a new project.

### ► **bada Shared Library**

This template is suitable for creating an application library with shared libraries. If you select this template, you need to make sure that the Linker of the IDE can access the external libraries at build time. Therefore, you need to define the path to the libraries in the project settings. When you build the project, the IDE creates the links to the external shared libraries.

### ► **bada Static Library**

This template is suitable for creating an application library with static libraries. If you select this template, you need to make sure that the Linker of the IDE can access the external libraries at build time. Therefore, you need to define the path to the libraries in the project settings. When you build the project, the IDE creates the links to the external static libraries.

### ► **bada Web Application**

This template is suitable for creating standalone bada Web applications using only Web standard technologies, such as HTML5, JavaScript, and CSS files. The template contains the bada 2.0 Javascript UI for the creation of Web applications with bada native look and feel.

## **Project files and folders**

As the `Share` folder is a reserved folder, a folder with this name cannot be created in the `/Home` default project directory. The `/src`, `/inc`, `/Home`, and `/Res` folders can contain files and folders with a `'` prefix; however, those files and folders are not copied to the target device. The `manifest.xml` and `application.xml` files are stored in the root folder of the project.