

1. Add a pop-up to the project by right-clicking Popups in the Resource Explorer and selecting New Popup.
2. Double-click the new pop-up instance in the Resource Explorer to open it in the work area.
3. Design the pop-up as you design a form. You can add controls to the pop-up from the ToolBox, and define properties for the pop-up and the added controls in the Properties view.

Once you have finished adding a pop-up to your application form, you can use the pop-up's ID (IDP_POPUP1 in the following example) to construct the pop-up in your application code:

```
• bool CommonPopup::Initialize()
• {
•     Popup::Construct(L"IDP_POPUP1");
•     SetName(L"CommonPopup");
• }
```

Using UI Controls

You can add UI controls to `Osp::Ui::Controls::Form` classes and define properties for them using the UI Builder.

To add and design a button:

1. In the bada IDE Project Explorer, select the application project.
2. Add the button by selecting it in the ToolBox and dragging and dropping it onto the form.
3. Set the properties of the button, such as its size and alignment, in the Properties view.
4. To place the button inside a container control (such as a panel), set the container name as the value of the button's Parent Name property.
5. To add event listeners for the button, right-click the button and select Add event handler. Select the listener to be added, enter an action ID in the Action ID field, and click Finish.

If you need multiple event listeners, add them one at a time to be able to define an action ID separately for each. The action IDs must be unique within a form.

Once you have finished adding the button to your form, you can use its ID (IDC_BUTTON1 in the following example) to construct the button in your application code:

```
• bool Form1::OnInitializing(void)
• {
```