

The UI is typically created using the UI elements provided in the `Ui` namespace, and the application must explicitly include the `Osp.Core` and `Osp.Ui` JavaScript files. The commonly used DOM APIs are available for the application.

► Without using the `Ui` namespace

You can code the application with commonly used constructs of HTML, CSS, or JavaScript. You can also use other frameworks, such as jQuery.

Building applications

In the bada IDE, different build configurations are available for different development steps:

► The Target-Debug build is used to debug and test the application with a target device and the Emulator.

The binary, data, and debug files are stored in a `.Target-Debug` folder under the project in the workspace. The external libraries used by your application are linked to the executable binary file and are copied to the target file system.

► The Target-Release build is used for the tested, release-ready version of the application.

The compiled binary file is stored in a `.Target-Release` folder under the project in the workspace.

Building the application in the IDE

To create an application project build, do one of the following:

1. Select the build configuration:
2. Right-click the project in the bada IDE Project Explorer.
 - a. Select **Build Configurations > Set Active**, and select the build configuration you need.
 - b. Build the application binaries for executing the code:
 - c. Select the project in the Project Explorer.
3. Select **Project > Build Project** in the menu.
 - a. Check your application project source code for any API or privilege violations, which are displayed in the Problems view.

Running and debugging applications

Debugging your application enables you to understand its flow of control. You can set breakpoints, step in, step out, and step over breakpoints, and watch variables to track the changes in their values.