

ronment, you can test your application before deploying it to the real target device.

▶ Target device

Running your application on a target device allows you to debug and test your application in a real-time environment.

Running C++ and Flash applications on the emulator

You can run bada C++ and Flash applications on the emulator using the Project Explorer or the bada IDE menu.

To run your application on the emulator:

1. Build the application.
 - a. If you use the Profiler tool, make sure the build configuration is Target-Debug.
2. Start the run by doing one of the following:
 - a. In the Project Explorer, right-click the project and select **Run As > bada Emulator Application**.
 - b. In the bada IDE menu, go to **Run > Run As > bada Emulator Application**.
 - c. The Emulator opens.
3. Use the application in the Emulator as you would in a target device.
 - a. While the application is running, the IDE's Output view shows the log, debug, and exception messages from the methods defined in the Log Macros.
 - b. While running the application, you can speed up repetitive tasks, such as login sequences, by using the UI Sequencer tool.
4. To terminate the run, do one of the following:
 - a. Click the Terminate button in the Console or Debug view.
 - b. Select Close from the Emulator menu.

Using the Emulator in Debugging

To debug your application with the Emulator:

1. To start debugging, right-click the project and select **Debug As > bada Emulator Application**.

The debug messages are displayed in the IDE's Console view. To see the GDB console, in the Console view, click the Display Selected Console button and select the option containing gdb. With the GDB console, you can also execute GDB commands.

Do not step out during debugging inside the **OspMain()** event handler in