

bada Emulator Web Application.

- In the bada IDE menu, go to Run > Run As > bada Emulator Web Application.

The Emulator opens.

2. Use the application in the Emulator as you would in a target device.

While the application is running, the IDE's Output view shows the log, debug, and exception messages.

To terminate the run, do one of the following:

1. Click the Terminate button in the Console or Debug view.

If the application execution is not suspended before you click the Terminate button, touch an arbitrary control on the screen or press a hard key on the Emulator after clicking Terminate.

2. Select Close from the Emulator menu.

Using the Emulator in Debugging

To debug your Web application with the Emulator:

1. To launch the application in the Emulator:

In the Project Explorer, right-click the project and select Run As > bada Emulator Web Application.

- In the bada IDE menu, go to Run > Run As > bada Emulator Web Application.

2. After the application has launched, start the JavaScript Debugger.

3. In the bada IDE menu, go to Run > Start JavaScript Debugging.

4. The JavaScript error and log messages are displayed in the JavaScript Debugger's Console panel.

To stop debugging, do one of the following:

1. In the bada IDE, in the Console or Debug view, click the Terminate button.

If the application execution is not suspended before you click the Terminate button, touch an arbitrary control on the screen or press a hard key on the Emulator after clicking Terminate.

2. On the Emulator, press the End key.

After debugging, run your application again to check its functionality and to ensure that the bugs detected during the debugging process are fixed.

Running C++ and Flash Applications on a Target Device

To run your application on a target device:

1. Connect the target device to your computer.
2. Configure the target device for running applications on it.
3. To use the Profiler tool, configure the application for profiling.