

3. Start the run by doing one of the following:

- In the Project Explorer, right-click the project and select `Run As > bada Target Web Application`.
- In the bada IDE menu, go to `Run > Run As > bada Target Application`.

The package (code and data files) is downloaded before starting the run, and the application is installed automatically while it runs.

While the application is running, the IDE's Output view shows the log, debug, and exception messages.

4. To terminate the run, do one of the following:

- In the bada IDE, click the Terminate button in the Console or Debug view.

If the application execution is not suspended before you click the Terminate button, touch an arbitrary control on the screen or press a hard key on the target device after clicking Terminate.

- On the target device, press the End key.

5. Disconnect the target device.

Using a Target Device in Debugging

To debug your application with a target device:

1. Connect the target device to your computer.
2. Configure the target device for debugging.
3. Launch the application by doing one of the following:

- In the Project Explorer, right-click the project and select `Run As > bada Target Web Application`.
- In the bada IDE menu, go to `Run > Run As > bada Target Application`.

4. Make sure that your current IP address is static. JavaScript debugging cannot be operated appropriately on a target device if your computer has a dynamic IP address.

5. After the application has launched, start the JavaScript Debugger.

In the bada IDE menu, go to `Run > Start JavaScript Debugging`.

The JavaScript error and log messages are displayed in the JavaScript Debugger's Console panel.

6. To stop debugging, do one of the following:

- In the bada IDE, in the Console or Debug view, click the Terminate button.

If the application execution is not suspended before you click the Ter-