

minate button, touch an arbitrary control on the screen or press a hard key on the target device after clicking Terminate.

- On the target device, press the End key.

7. Disconnect the target device.

After debugging, run your application again to check its functionality and to ensure that the bugs detected during the debugging process are fixed.

Packaging applications

After your application has been successfully tested on the Emulator and the target device, you need to package it. You can package your application using bada IDE, or use a command line command to build and package it at the same time. The command line is only available for C++ and Flash applications.

The C++ and Web frameworks use the same packaging format, however, the Web framework has a few extensions. For example, you can provide a network access control list (which defines the domains that are allowed to access the network) in the /Res/config.xml file of the Web application. The web application package does not contain any C++ source code files or binaries.

Packaging Applications with the bada IDE

In case of a web application, skip steps 1 and 3a.

In order to package your application using bada IDE:

1. If you have made changes to the application after testing it, re-build the application.
2. Package your application by first selecting the project in the Project Explorer and then selecting **Project > Make Package** in the menu.
3. In the Make Package window:
 - a. Select Target-Debug or Target-Release as the configuration.
 - b. Select the files and folders to include in the bada application package file.
 - c. Enter a name for the application package and select an output folder.
 - d. Click Make to proceed with the creation of the package.

The application package, by default <application>_<buildconfiguration>.zip (for the C++ framework) or <application>_Target-Release.zip (for the Web framework), is stored under the project folder. The package automatically includes all the required files: the binaries (.exe and .dll files), resources and the manifest.xml and application.xml files.

4. Check the package in the project folder to ensure that the packaging