

the IDE, with default content in the application.xml file as well as in several project folders. The selectedmanifest.xml file is also included in the project.

4. Creating the application code

Your HelloWorld project uses the Form Based Application template. As such, your project's source files already contain some of the basic application functionality.

The automatically-included code creates an application with the title "Hello bada". To change the title to HelloWorld, take the following steps:

1. Select IDF_FORM1 (1).
2. Select the header (2).
3. Select the Properties view (3).
4. Scroll down the Properties view until you find the Title Text row. Change "Hello bada!" to "HelloWorld" (4).

Basic app

This chapter, based on the BasicApp sample delivered with the bada SDK in <BADA_SDK_HOME>\Samples\BasicApp, demonstrates how you can use the `Osp::Ui` namespace to implement the basic UI functionalities in the bada C++ application.

Basic App - Form

The BasicApp sample application uses the bada Form Based Application template, which contains a preset `Osp::Ui::Controls::Form` class. Most methods used in the sample remain as they were created in the project template.

To Initialize the Application

- a. The header file declares the form and listener interface used by the `MainForm` class. The application functionality requires the `Osp::Ui::IActionEventListener` interface to be defined to listen to button and footer item events, allowing other parts of the application to react to them.

```
class MainForm:
{
public Osp::Ui::Controls::Form,
public Osp::Ui::IActionEventListener
```

- b. A common way to map functions to specific UI controls is to use action IDs, such as in the following snippet. The `ID_FOOTER_ITEM*` values