

ShowState() method to show the current panel on the screen.

```
// Set the current panel as selected in the footer and
display it on the form
if(pFooter)
{
    pFooter->SetItemSelected( __ _panelId);
    if( __ _panelId == 2)
        SetOrientation(ORIENTATION _ AUTOMATIC);
    __ _pPanel[0]->SetShowState(false);
    __ _pPanel[1]->SetShowState(false);
    __ _pPanel[2]->SetShowState(false);
    __ _pPanel[3]->SetShowState(false);
    __ _pPanel[ __ _panelId]->SetShowState(true);
}

Draw();
Show();

return r;
}
```

- The OnTerminating() event handler is called each time a panel is terminated. At this point, the current application settings (the latest used panel) are saved to the application registry, which can be used to restore the settings the next time the application is executed.

Respond to Action events

The OnActionPerformed() event handler uses the switch-case structure to define the action that occurs when the UI controls are triggered (a footer item or the button on the Orientation panel is clicked). The triggers are recognized by the source and action ID parameters passed to this event handler.

```
void MainForm::OnActionPerformed(const Osp::Ui::Control&
source, int actionId)
{
    switch(actionId)
    {
        case ID _ FOOTER _ ITEM1:
        {
            __ _pPanel[0]->SetShowState(true);
        }
    }
}
```