

is launched: `Initialize()` and `OnInitializing()`. The `Initialize()` method constructs a rectangular panel.

result `ImagePanel::Initialize(Osp::Graphics::Rectangle rect)`

```
• {
•     result r = E_SUCCESS;
•
•     Panel::Construct(rect);
•
•     return r;
• }
```

2. The `OnInitializing()` event handler deals with decoding the given image into the desired bitmap format using the `DecodeN()` method.

result `ImagePanel::OnInitializing(void)`

```
• {
•     result r = E_SUCCESS;
•
•     Image image;
•     image.Construct();
•     __pBadaBitmap = image.DecodeN(L"/Res/ScreenDensity-
High/bada.png",
•                                     BITMAP_PIXEL_FORMAT_
ARGB8888);
•
•     return r;
• }
```

3. The `OnDraw()` event handler requests for the current canvas (`GetCanvasN()`), the location and size of the canvas (`GetBounds()`), and the orientation status of the screen (`GetOrientationStatus()`).

Based on the value returned by the `GetOrientationStatus()` method, the bitmap image is drawn on the screen using the `DrawBitmap()` method.

result `ImagePanel::OnDraw(void)`

```
• {
•     result r = E_SUCCESS;
•     Form *pForm = static_cast<Form *>(GetParent());
•
•     Canvas* pCanvas = GetCanvasN();
•     Rectangle rt = pCanvas->GetBounds();
•
• }
```