

```

    if(pCanvas != null && __pBadaBitmap != null)
    {
        Rectangle clientRect = pForm->GetClientAreaBounds();
        Rectangle rt(0, 0, clientRect.width, clientRect.
height);
    }

    OrientationStatus status = pForm-
>GetOrientationStatus();

    // Fill the client area with the bitmap with aspect
ratio maintained
    if(status == ORIENTATION _ STATUS _ PORTRAIT
    || status == ORIENTATION _ STATUS _ PORTRAIT _
REVERSE)
    {
        int width = rt.width;
        int height = rt.width*__pBadaBitmap-
>GetHeight()/__pBadaBitmap->GetWidth();
        pCanvas->DrawBitmap(Rectangle(rt.x, (rt.y + ((rt.
height-height)/2)),
                                width, height), * __pBada-
Bitmap);
    }
    else if(status == ORIENTATION _ STATUS _ LANDSCAPE
    || status == ORIENTATION _ STATUS _ LAND-
SCAPE _ REVERSE)
    {
        int height = rt.height;
        int width = rt.height*__pBadaBitmap-
>GetWidth()/__pBadaBitmap->GetHeight();
        pCanvas->DrawBitmap(Rectangle((rt.x+((rt.width-
width)/2)), rt.y,
                                width, height), * __pBada-
Bitmap);
    }
    delete pCanvas;
}

return r;
}

```

4. The OnOrientationChanged() event handler changes