

- `});`

Static members can be accessed by using the fully-qualified class name. They cannot be inherited.

- `var foo = Osp.Test.Cat.LEGS;`
- `alert(Osp.Test.Cat.makeSound());`

▶ **Instance members** are assigned to each individual instance of a class. An instance member of a class can be an instance variable or an instance method. Instance members are declared in the members section of the class definition:

- `Osp.Class.define("My.Cool.Class",`
- `{`
- `members:`
- `{`
- `foo: VALUE,`
- `bar: function() { }`
- `}`
- `});`

The instance members can be accessed by using an actual instance of a class:

- `var myClass1 = new My.Cool.Class;`
- `myClass1.foo = 3.141;`
- `myClass1.bar();`

Data and access types

The web framework supports two data types, which provide fundamentally different behaviours:

▶ **Primitive types** include Boolean, Number, String, null, and undefined. If a primitive type is assigned to an instance variable in the class declaration, the variable behaves as if each instance has a copy of that value. Primitive types are never shared among instances.

▶ **Reference types** include Array, Function, RegExp, and the generic Object. Reference types point to a corresponding data value that represents a more complex data structure than the primitive type. If such a reference type is assigned to an instance variable in the class declaration, the variable behaves as if each instance is pointed to the same complex data structure. All instances share the same value, unless the corresponding instance variable is assigned a different value. As all reference data types are shared by default, be careful when using them in the class declaration.