

can associate with only one container instance. A container, however, can have at most two layout instances associated with it, one for each orientation mode: portrait and landscape.

For applying any layout to a container, an instance of the layout is first created. This layout instance is then passed as a value to the 'layout' key in the container constructor, thus associating it with the container.

```
• var relativeLayout = new Osp.Ui.RelativeLayout();
• var panel = new Osp.Ui.Controls.Panel
• ({
•   bounds: {x: 20, y: 40, width: 40, height: 50},
•   groupStyle: "single", layout: relativeLayout
• });
```

When a layout is associated with a container, the settings of a control that is present inside the container change according to the rules specified for the layout. No explicit method call is required to apply the layout. The application of the layout rules is done implicitly as soon as the layout is associated with the container.

HelloWorld tutorial

Let's look at creating a simple HelloWorld application. Read this chapter to help familiarise yourself with the bada web application development process as well as with using the bada SDK by creating a simple HelloWorld application that contains the basic bada web application functionality and displays a form on the device screen.

To create a HelloWorld application

1. Creating the application profile

Define your application details on the bada developer site and download the manifest file. To get familiar with the IDE and SDK, you can create the HelloWorld application without registering it on the bada developer site. When creating an application without registration, use the default manifest file provided in the SDK.

2. Creating the HelloWorld Project

- a. Launch the IDE by selecting `Start > Programs > bada SDK > badaIDE`.
- b. Create the application project in the IDE.

During the project creation, define HelloWorld as the name of your project, and select the downloaded manifest file (if you downloaded one