

you can use the `Osp.Ui` namespace to implement the basic UI functionalities in the bada web application.

To initialise the application

1. BasicApp.js source file

a. The `define()` method of the `Osp.Core.Class` class is used to create the main class of the application (`Ba.BasicApp`) with a specific configuration. The following configuration parameters are set for the application:

- The `extend` key is used to inherit the `Osp.Core.Object` class.
- The `include` key is used to add the `BasicAppAllPanels` mixin to the application. The `BasicAppAllPanels` mixin is defined in the `BasicAppAllPanels.js` source file to merge or mix its code logic and variables with the `BasicApp.js` file.
- The `construct` key represents the class constructor which, in this case, retrieves the instance of the `Osp.Ui.Controls.Frame` class.
- The `members` key is used to declare and define the required constant members, which define the panel, button, and image label dimension constants in the application, as well as the location of the image used on the Image panel and the action IDs for reacting to footer item clicks.

```
Osp.Core.Class.define("Ba.BasicApp",
{
  extend: Osp.Core.Object,
  include: [BasicAppAllPanels],
  construct: function(frameObj)
  {
    this.frameObj = Osp.Ui.Controls.Frame.getInstance();
  },
  members:
  {
    CONST:
    {
      ID_IMAGE_PATH: '../Res/BasicWebApp/image/',
      PANEL_WIDTH: 480,
      PANEL_HEIGHT: 630,
      BUTTON_X: 10,
```