

- `});`

The `addControl()` method of the `Frame` class is used to add the created form to the application frame. The form is set as the current form using the `setCurrentForm()` method.

- `Osp.Ui.Controls.Frame.getInstance().addControl(this.basicForm);`
- `this.frameObj.setCurrentForm(this.basicForm);`
- `this.createHeader();`
- `this.createFooterButtons();`
- `},`

2. Setting the Footer Content

The `getCurrentForm()` and `getFooter()` methods are used to retrieve the current form and the `Osp.Ui.Controls.Footer` instance. The tab footer style is set for displaying the footer items that allow the user to access the four panels.

- `createFooterButtons: function()`
- `{`
- `vCurrForm = (Osp.Ui.Controls.Frame.getInstance()).getCurrentForm();`
- `footer = vCurrForm.getFooter();`
-
- `footer.setFooterStyle(Osp.Ui.Controls.FooterStyle.TAB);`

An action ID and name is set for each of the four tab footer items created using the entries from an array. The name determines the text shown on the tab on the screen, and the action ID is later used to identify the individual items in the `onActionPerformed()` event handler, which defines the action events that can be triggered for the items.

The `setItemSelected()` method sets the first tab as selected, which means that the `Button` panel is the first screen to be displayed. The `addItem()` method is used to add all the footer items to the footer. Finally, an event listener is added to the footer for responding to action events.

- `aForm = new Array("Button", "Orientation", "Image", "Privilege");`
- `for(var i = 0; i < aForm.length; i++)`
- `{`
- `footerItem =`
- `{`
- `actionId: i+1,`