

```

    text: aForm[i],
  };
  footer.setItemSelected(0);
  footer.addItem(footerItem);
}
footer.addListener('actionPerform', this.onActionPer-
formed, this);
},
3.Setting the Header Content
The getHeader() method of the Form class is used to get
the Osp.Ui.Controls.Header class instance. The setTitle-
Text() method sets a title to be displayed in the header.
createHeader:function()
{
  this.basicForm.getHeader().setTitleText("Basic WebApp");
},

```

Respond to Action Events

1. BasicApp.js Source File

Based on the action IDs, the `onActionPerformed()` event handler triggers a set of actions. For each footer tab, it sets the footer tab as selected, the applicable panel as visible, and the other panels as invisible. It also sets the orientation of the form, and defines other panel-specific settings, as needed.

```

onActionPerformed: function(e)
{
  switch(e.getData().actionId)
  {
    case this.CONST.ACTIONID _ FOOTER.BUTTON _ PANEL:
      this.privilegePanel.setVisible(false);
      this.imagePanel.setVisible(false);
      this.orientationPanel.setVisible(false);
      this.buttonPanel.setVisible(true);
      this.basicForm.setOrientation(Osp.Ui.Orientation.
PORTRAIT);
      Osp.Ui.Controls.Frame.getInstance().getCurrent-
Form().getFooter().setItemSelected(0);

      break;

      // Other cases are defined here
  }
}

```