

Panel panel and its content. An instance of the `Osp.Ui.RelativeLayout` class is created. The `RelativeLayout` class allows UI controls to be aligned with respect to each other.

```
• createBodyButtonPanel: function()
• {
•     this.relativeLayoutButtonPanel = new Osp.
Ui.RelativeLayout();
```

An `Osp.Ui.Controls.Panel` instance is created by specifying the boundaries of the panel, and the common panel layout for both portrait and landscape orientation modes. The `setBackgroundColor()` method sets the background color of the panel to black.

```
•     this.buttonPanel = new Osp.Ui.Controls.Panel
•     ({
•         bounds:
•         {
•             x: 0,
•             y: 0,
•             width: this.basicForm.getClientAreaBounds().width
•         },
•         height: this.basicForm.getClientAreaBounds().
height
•     },
•     layout: this.relativeLayoutButtonPanel
• });

•     this.buttonPanel.setBackgroundColor("black");
```

An instance of the `Button` class is created by specifying the size of the button, the button text, and an action ID for the button.

A `Label` instance is created by setting its bounds, width, height, and text. The text color and size of the label is set using the `setTextColor()` and `setTextSize()` methods, respectively.

```
•     this.labelButton = new Osp.Ui.Controls.Button
•     ({
•         bounds:
•         {
•             x: this.CONST.BUTTON_X,
•             y: this.CONST.BUTTON_Y,
•             width: this.CONST.BUTTON_WIDTH,
•             height: this.CONST.BUTTON_HEIGHT
```