

```

•   this.relativeLayoutButtonPanel.setRelation(this.demo-
Label, this.labelButton,
•   Osp.
Ui.RectangleEdgeRelation.RECT _ EDGE _ RELATION _ BOTTOM _ TO _
TOP);
•   },

```

Create the orientation panel

The Orientation screen demonstrates the orientation-related features in bada web applications.

The `createBodyPanelOrientation()` method is used to create the `orientationPanel` panel and its content. Similarly to the `buttonPanel` panel, this panel contains a relative layout and a button.

```

•   createBodyPanelOrientation:function()
•   {
•       // UI elements are created here
•       An event listener is set for the form to listen to
changes in the device orientation.
•       this.basicForm.addListener('orientationChange',
function(e)
•       {
•           this.changeOrientation();
•       },
•       this);
•   },

```

When the `changeOrientation()` method is called, it is a trigger to change the orientation from portrait to landscape or vice versa.

The `setBounds()` method sets the current boundaries of the `orientationPanel` instance. The `getOrientationStatus()` method is used to get the current orientation of the form.

```

•   changeOrientation: function()
•   {
•       this.orientationPanel.setBounds
({
•       x: 0,
•       y: 0,
•       width: this.basicForm.getClientAreaBounds().width,
•       height: this.basicForm.getClientAreaBounds().height
•   });

```