

```

•   ({
•       bounds: {x: 0, y: 0, width: 0, height: 0}, text: ""
•   });
•   this.demoLabelImagePanel.setBackgroundImage(this.CONST.
ID _ IMAGE _ PATH + "bada.png");
•   The width and height of the label containing the back-
ground image is set using the setWidth() and setHeight() me
thods, respectively.
•   this.relativeLayoutImagePanelPortrait.setWidth(this.
demoLabelImagePanel,
•
•                               this.
CONST.IMAGE _ LABEL _ WIDTH);
•   this.relativeLayoutImagePanelPortrait.setHeight(this.
demoLabelImagePanel,
•
•                               this.
CONST.IMAGE _ LABEL _ HEIGHT);
•
•   // Set the panel alignment and add orientation change
listener
• },

```

Create the Privilege Panel

The Privilege screen demonstrates the use of system privileges in bada web applications. It attempts to use methods that require certain privilege groups, and tests whether the application has the required privileges.

The screen contains a panel and two labels and buttons, created similarly as for the other screens.

The two methods that require privileges are the `getPropertyValue()` method of the Device Status WAC module and the `getTaskLists()` method of the Task WAC module, called by the `testButton1` and `testButton2` button presses, respectively.

Only the `getPropertyValue()` method (used to retrieve the current battery level) is successful, since its required privilege has been set in the manifest file.

```

•   actionPerformedPrivilegePanel: function(e)
•   {
•       switch(e.getData().actionId)
•       {
•           case this.ACTION _ ID.PRIVILEGE _ TEST _ 1:
•               this.demoLabel3.setText("Success");

```