

- `#include "GlesCube.h"`
- `#include "fragment.h"`
- `#include "vertex.h"`
- `#include <math.h>`

- Various arrays are also defined within the `GlesCube.cpp` file:
 - In a vertices array, each group of 3 values defines 1 of the 8 vertices of the cube. The values for the 8 vertices of the cube have been defined 3 times to reduce the number of times the array is called in the application.
 - A colors array defines a color for each vertex defined in the vertices array.
 - An indices array defines the links between all the available vertices defined in the vertices array. This array helps in reducing redundancy in defining the number of vertices of the cube.

To Initialize EGL™

1. GlesCube.cpp Source File

- The `eglConfigList[]` list is used to define the EGL™ configuration requirements for the application. In this case, the required configuration consists of the following:
 - 16-bit RGB565 format color scheme
 - Window as a selected screen
 - Support for OpenGL® ES 2.0

The `EGL_NONE` value indicates the end of the configuration list. It must always be the last element of the list.

```
bool GlesCube::InitEGL()
{
    EGLint numConfigs = 1;
    EGLint eglConfigList[] =
    {
        EGL_RED_SIZE, 5,
        EGL_GREEN_SIZE, 6,
        EGL_BLUE_SIZE, 5,
        EGL_ALPHA_SIZE, 0,
        EGL_DEPTH_SIZE, 8,
        EGL_SURFACE_TYPE, EGL_WINDOW_BIT,
        EGL_RENDERABLE_TYPE, EGL_OPENGL_ES2_BIT,
        EGL_NONE
    };
}
```