

- `return true;`
- `}`

Draw the GlesCube

1. GlesCube.cpp Source File

- The `glViewport()` method specifies the affine transformation of the x and y values from normalized device coordinates to window coordinates as specified by the `GetBounds()` method.

Normalized device coordinates are a part of a device-independent coordinate system which is used to ensure that the application runs smoothly on different devices with different aspect ratios.

Affine transformation is a combination of single transformations, such as rotation or reflection on an axis.

```
• bool GlesCube::Draw()
• {
•     int x, y, width, height;
•     __pForm->GetBounds(x, y, width, height);
•
•
•
•     glViewport(0, 0, width, height);
•
•
•     glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT | GL_STENCIL_BUFFER_BIT);
```

- The `glVertexAttribPointer()` method is used to define an array of generic vertex attribute data. These attributes are parameters (in this case, position and color) associated with each vertex of the cube. In both instances, the final parameter (vertices and colors) represent the previously defined arrays - vertices and colors.

The `glEnableVertexAttribArray()` method enables the generic vertex attribute data arrays. These enabled attributes can be accessed and used to render the scene.

```
• glVertexAttribPointer(__idxPosition, 3, GL_FLOAT,
GL_FALSE, 3 * sizeof(GL_FLOAT),
•     vertices);
• glVertexAttribPointer(__idxColor, 4, GL_FLOAT, GL_
FALSE, 4 * sizeof(GL_FLOAT),
•     colors);
```