

```

xmlns:em="http://www.mozilla.org/2004/em-rdf#"

<Description about="urn:mozilla:install-manifest">
  <em:id>sample@example.net</em:id>
  <em:version>1.0</em:version>
  <em:type>2</em:type>

  <!-- Target Application this extension can install into,
        with minimum and maximum supported versions. -->
  <em:targetApplication>
    <Description>
      <em:id>{ec8030f7-c20a-464f-9b0e-13a3a9e97384}</em:id>
      <em:minVersion>1.5</em:minVersion>
      <em:maxVersion>4.0.*</em:maxVersion>
    </Description>
  </em:targetApplication>

  <!-- Front End MetaData -->
  <em:name>sample</em:name>
  <em:description>A test extension</em:description>
  <em:creator>Your Name Here</em:creator>
  <em:homepageURL>http://www.example.com/</em:homepageURL>
</Description>
</RDF>

```

-
- </code>

Note that not all of these properties are required. The ‘won’t-build-if-absent’ properties include:

1. **id:** An identifier for the add-on, which can be a GUID or an email address formatted as a string
2. **version:** The version of the extension being supplied
3. **type:** The kind of code being supplied, with 2 representing an add-on, 4 for theme, 8 for a locale, 32 for a Multiple Package Item, and 64 for a spell-check dictionary
4. **targetApplication:** The application that you’re building the extension for, such as Firefox or ThunderBird
5. **name:** The name of the add-on

The rest are optional properties, but it’s advisable to supply as much information as you can, so as to make the code more accessible, and also to aid the process of review at AMO (addons.mozilla.org).