

enter “chrome://browser/content/browser.xul” into the Firefox address bar, and see what happens (nothing bad, we promise!).

Chrome URIs consist of several components:

1. **The URI scheme (chrome):** which tells Firefox’s networking library that this is a Chrome URI. It indicates that the content of the URI should be handled as a chrome. Compare chrome to http which tells Firefox to treat the URI as a web page.
2. **A package name (in the example above, browser):** which identifies the bundle of user interface components. This should be as unique to your application as possible to avoid collisions between extensions.
3. **Type of data being requested:** There are three types: content (XUL, JavaScript, XBL bindings, etc. that form the structure and behavior of an application UI), locale (DTD, .properties files etc. that contain strings for the UI’s localisation), and skin (CSS and images that form the theme of the UI).
4. **The path of a file to load**

Chrome manifest

comments

A line is a comment if it begins with the character ‘#’. Any other character in the line is ignored.

- `# this line is a comment - you can put whatever you want here`

manifest

- `manifest subdirectory/foo.manifest [flags]`

This will load a secondary manifest file. This can be useful for separating component and chrome registration instructions, or separate platform-specific registration data.

binary-component

- `binary-component components/mycomponent.dll [flags]\`

Instructs Mozilla to register and use a binary component. It should be combined with the ABI flag, since binary components are ABI-specific. Prior to Firefox 4, files in the components directory were registered automatically.

interfaces

- `interfaces component/mycomponent.xpt [flags]`