

Instructs Mozilla to load interface information from a typelib file produced by XPIDL. Prior to Firefox 4, files in the components directory were registered automatically.

component

- `component {00000000-0000-0000-0000-000000000000} components/mycomponent.js [flags]`

Informs Mozilla about a component CID implemented by an XPCOM component implemented in JavaScript (or another scripting language, if applicable). The ClassID {0000...} must match the ClassID implemented by the component. To generate a unique ClassID, use a UUID generator program or site.

contract

- `contract @foobar/mycontract;1 {00000000-0000-0000-0000-000000000000} [flags]`

Maps a contract ID (a readable string) to the ClassID for a specific implementation. Typically, a contract ID will be paired with a component entry immediately preceeding.

category

- `category category entry-name value [flags]`

Registers an entry in the category manager. The specific format and meaning of category entries depend on the category.

content

A content package is registered with the line

- `content packagename uri/to/files/ [flags]`

This will register a location to use when resolving the URI `chrome://packagename/content/...`. The URI may be absolute or relative to the location of the manifest file. Note: it must end with a '/

locale

A locale package is registered with the line

- `locale packagename localename uri/to/files/ [flags]`

That's about it, as far as the absolute essential (non-code) files go. You're free to add many more, of course. For example, you may want your extension to be a restartless service, which means that the browser doesn't need