

<textbox type="password">

A textbox that hides the characters typed; used for entering passwords.

<textbox type="search">

A textbox for searching.

<timepicker>

A timepicker displays a set of textboxes for entering a time.

<toolbarbutton>

A button that is displayed on a toolbar.

<toolbarbutton type="menu">

A button that is displayed on a toolbar with a dropdown menu attached to it.

<toolbarbutton type="menu-button">

A button on a toolbar that has a separate arrow button with a menu attached to it. Unlike with the 'menu' type, a separate action may be performed when the main part of the button is pressed.

<tree>

A tree displays a hierarchy of items in multiple columns.

Overall, the various groups that you have access to here are:

- ▶ **Top-level elements:** window, page, dialog, wizard, etc.
- ▶ **Widgets:** label, button, text box, list box, combo box, radio button, check box, tree, menu, toolbar, group box, tab box, colorpicker, spacer, splitter, etc.
- ▶ **Box model:** box, grid, stack, deck, etc.
- ▶ **Events and scripts:** script, command, key, broadcaster, observer, etc.
- ▶ **Data source:** template, rule, etc.
- ▶ **Others:** overlay, iframe, browser, editor, etc.

An important feature, which should be rather intuitive when you realise that XUL is basically just an XML dialect, is that one can use elements from other applications of XML within XUL documents, such as XHTML, SVG, and MathML. Another innovation in this regard is Mozilla's addition of some common widgets with Gecko 1.9 such as `<scale/>` (sometimes called "slider"), `<textbox type="number"/>` (spinbox), time and date pickers. You can have the power of full-blown web apps and such, with all the benefits of local applications. Truly the best of both worlds and then some!