

```

• <Description about="urn:mozilla:install-manifest">
•   <em:id>testapp@watteimdocht.de</em:id>
•   <em:name>Testapp</em:name>
•   <em:description></em:description>
•   <em:version>0.1</em:version>
•   <em:creator>Fabian Franzen</em:creator>
•   <em:homepageURL>http://www.watteimdocht.de/test</
em:homepageURL>
•   <em:type>2</em:type>
•
•   <!-- Mozilla Firefox -->
•   <em:targetApplication>
•     <Description>
•       <em:id>{ec8030f7-c20a-464f-9b0e-13a3a9e97384}</
em:id>
•       <em:minVersion>4.0</em:minVersion>
•       <em:maxVersion>25.*</em:maxVersion>
•     </Description>
•   </em:targetApplication>
• </Description>
• </RDF>
•
• </code>

```

This kind of file is called the Install Manifest, which, as we know, is the metadata holder for the packaged add-on. This RDF file, of course, could be a lot more (and, on the other end, a lot less) descriptive about the add-on, with a structure that we've already seen in the previous chapters. Still, with the file being a necessity for any architecture that builds into a Firefox extension, we declare it here, with some of the essential values.

Next up, we look at the required structure that the rest of the add-on needs to follow. An important file here is the Chrome Manifest (`chrome.manifest`). This file declares the chrome resources that the add-on will be using, and that's what we see in action in the following piece of code.

```

• <code>
•
• content    xulschoolhello                content/
•
• overlay chrome://browser/content/browser.xul chrome://

```