

nations. To define a hotkey combination, create a Hotkey object, passing it the combination and a function to be called when the user presses that combination.

indexed-db

The indexed-db module exposes the IndexedDB API to add-ons. Scripts running in web pages can access IndexedDB via the window object. Note that it's still in experimental stages of implementation.

l10n

The l10n module enables add-ons to localise strings appearing in the add-on's JavaScript code. Note that you can't currently use localise strings appearing in content scripts or HTML files.

notifications

The notifications module allows you to display transient, toaster-style desktop messages to the user.

page-mod

The page-mod module enables you to run scripts in the context of specific web pages. To use it, you specify:

- ▶ one or more scripts to attach. The SDK calls these scripts 'content scripts'.
- ▶ a pattern that a page's URL must match, in order for the script(s) to be attached to that page.

page-worker

The page-worker module provides a way to create a permanent, invisible page and access its DOM (Document Object Model). The module exports a constructor function 'Page', which constructs a new page worker. A page worker may be destroyed, after which its memory is freed, and you must create a new instance to load another page.

panel

This module exports a single constructor function 'Panel' which constructs a new panel. A panel is a dialog. Its content is specified as HTML and you can execute scripts in it, so the appearance and behaviour of the panel is limited only by what you can do using HTML, CSS and JavaScript.