

content/mod

The mod module provides functions to modify a page content.

content/symbiont

The symbiont module exports the Symbiont trait, which is used in the internal implementation of SDK modules such as panel and page-worker, that can load web content and attach content scripts to it.

content/worker

This module is used in the internal implementation of SDK modules which use content scripts to interact with web content such as the tabs, panel, or page-mod modules.

core/heritage

Doing inheritance in JavaScript is both, verbose and painful. Reading or writing such code requires a sharp eye and lots of discipline, mainly due to code fragmentation and lots of machinery being exposed, which is why this module provides a minute degree of control over the same.

core/namespace

Provides an API for creating namespaces for any given objects, which effectively may be used for creating fields that are not part of objects' public API.

core/promise

With most JS APIs being asynchronous, callbacks are the law of the land, but are rather difficult to maintain. Now, consider the scenario where instead of continuation passing via callback, function returns an object, that represents eventual result, either successful or failed. This object is a promise, both figuratively and by name, to eventually resolve. We can call a function on the promise to observe either its fulfillment or rejection. If the promise is rejected and the rejection is not explicitly observed, any derived promises will be implicitly rejected for the same reason. This functionality is provided by the module core/promise.

event/core

Many modules in the SDK can broadcast events. For example, the tabs module emits an open event when a new tab is opened. The event/core module enables you to create APIs that broadcast events. Users of your