

```

    • "description": "Hide the navigation bar for every app
tab",
    • "license": "MPL 1.1/GPL 2.0/LGPL 2.1",
    • "author": "Felipe Gomes",
    • "version": "1.0.1",
    • "fullName": "Aaapptabs",
    • "id": "jid0-4lCWKLkuXBNbApFwqYAr8GZdNas",
    • "name": "aaapptabs"
  }
  •
  • </code>

```

Simple enough, right? The only nondescript part is the ugly-looking code under the 'id' property. But then what's the SDK for if not to protect you from the ugliness? It does its job well, supplying that value (which by the way, is a Firefox identifier) beforehand, at initialisation. Leave a file that looks something like this, at the root of your extension's directory.

Now, we move on to the first point of contact between the browser and the add-on in the Jetpack scenario, the 'main.js' file. Located inside the root/lib folder, this is where the execution starts, and continues unless you make an effort to include some other elements of code in the process. Mainly a standard JavaScript file, let's look at a sample of what it should look like. Here's a snippet of code from the add-on that we're examining at the moment:

```

  • <code>
  •
  • const wu = require("window-utils");
  •
  • let mappings = [];
  •
  • function start(chromeWindow) {
  •   let XULBrowserWindow = chromeWindow.XULBrowserWindow;
  •   if (XULBrowserWindow == undefined) {
  •     return;
  •   }
  •
  •   let originalFunction = XULBrowserWindow.hideChromeFor-
Location;
  •
  •

```