

```

•   transmission = {};
// A hash that will hold all values to be sent
•
•   transmission["version"] = brandShortName;
•
•
•   </code>

```

First, let's declare a few variables that we'd need to use over the course of building this add-on. We'll set up holders which will allow us to access the chrome's properties. For those of you who are doing this for the first time, 'chrome' here refers to all the elements in the browser's visible area, that is the user interface.

Then, we'll create accessors for the 'tabs' and data functions we'll make use of. While the 'data' accessor is used to maintain a link with the data/ folder that we had previously created, the 'tabs' accessor will give us the ability to manipulate tabs in a browser, both actively and passively. The brandStringBundle gives the ability to sense which browser we're running the code in. Among many possible release versions of Firefox, this includes Firefox Nightly and Firefox Aurora. Then, we'll set up a few other variables that would be important in the upcoming lines.

```

•   <code>
•
•   let toolbarButton = require('toolbarbutton').Toolbar-
Button({
•   id: "stats-toolbar-button",
•   label: "How we doin'?",
•   tooltipText: statsFullName,
•   image: data.url("chart-icon.png"),
•   onCommand: function () {
•       let aboutStatsAlreadyOpen = false;
•
•       // Check to see if aboutStatsUrl is already open in
one of the tabs
•
•       for each (let tab in tabs) {
•           if (tab.url.toLowerCase() == aboutStatsUrl) {
•               aboutStatsAlreadyOpen = true;

```