

If you look at the HTML page, you'll see that we're now starting to handle the wrapper divs that we'd declared there. Then, there are some other extractor functions that would be useful in tackling with and applying the data onto the chart when we eventually are ready to have one. For now, we're just declaring the entities to modulate the code structure, and have all that we need in the namespace. We've created the groundwork for the first visualisation which will be fed by the internal data from the single reporters.

```

<code>
•
•   var arcs = vis1.selectAll("g.slice")
•     .data(pie) //associate the generated pie data
•     .enter() /*this will create <g> elements for every
"extra" data element that should be associated with a
selection.
• The result is creating a <g> for every object in the data
array*/
•     .append("svg:g") //create a group to hold each slice
(we will have a <path> and a <text> element associated with
each slice)
•     .attr("class", "slice"); //allow us to style things
in the slices (like text)
•
•   var div = d3.select("#wrapper").append("div")
•     .attr("class","tooltip")
•     .style("opacity",1e-6);
•
•   arcs.append("svg:path")
•     .attr("fill", function(d, i) { return color(i); } )
•     .attr("d", arc) //actual SVG path created here
•     .on("mouseover", function(d) { d3.select(this).
style("fill", "white"); mouseover(); })
•     .on("mousemove", mousemove)
•     .on("mouseout", function(d, i) {d3.select(this).
style("fill", color(i)); mouseout(); });
•
</code>

```

As you can see, we're now creating the actual arcs that would be holding the data. But what good is a data projection if we don't know what that