



### Uber Lite

Uber has announced Uber Lite which is just 5MB in size and will work even if the users have slow internet connectivity. <https://dgit.in/jul18-43-1>



### Titan Underwater drone

Titan, an underwater drone on Kickstarter, promises to go approx. 150 meters into the waters. <https://dgit.in/jul18-43-2>

Now there are a set of methods that are available for maps. To access the value of a map's key you can either use the dot notation or the square bracket notation. Use dot notation when you know the value of the key.

But in case you don't know and it is stored within a variable then use the square bracket notation. Both notations are shown in a code sample at: <https://dgit.in/Groovy19>.

To add a value dynamically you can use the `.put` method. To check whether a key is there use `.containsKey` and to check whether a value is there use `.containsValue` method. To know the size of the map use the `.size` method.

Check out examples of these methods here: <https://dgit.in/Groovy20>. The output for the example code can be found here: <https://dgit.in/GrvyOP5>.

## CONDITIONALS AND LOOPING

Groovy supports every conditional aspects of Java and maybe even beyond that. `If-else` and `case` in Groovy works like Java. But `switch case` is more robust and can handle any kind of value that can be passed inside the switch in the code.

From the code at <https://dgit.in/Groovy21> you can see that switch can handle a host of values – from ranges to lists to datatypes to closures to regex. At the end, if none of them match the conditions in the switch then the default case is executed. The above code will generate this:

```
Do For Some Condition
Result => number
```

Groovy has support for ternary as well as elvis operator, as shown here: <https://dgit.in/Groovy22>. Ternary executes the first statement if true and the second if false. In Elvis the condition is matched – if it returns `true` or `not null` then the value is passed or else the default value (In this case “Anonymous”) is passed. Output is as shown below:

```
Value => First
Name => Anonymous
```

In Groovy Looping is done via `for` loop and it's variants, `while` and `do-while` loop. The examples are self explanatory and can be easily understood, as shown here: <https://dgit.in/Groovy23>. The output generated can be found at: <https://dgit.in/GrvyOp6>.

## CLOSURES

A closure in Groovy is an open, anonymous, block of code that can take arguments, return a value and be assigned to a variable. A closure may reference variables declared in its surrounding scope. In opposition to the formal definition of a closure, a closure in the Groovy language can also contain free variables which are defined outside of its surrounding scope.

Closure is one of the most important concepts of Groovy programming language. You can think of closures as lambdas or arrow functions. The code sample for closures is shown here: <https://dgit.in/Groovy24>. The code sample will generate the following output

```
Hellow World
Hellow World
Hellow Agnibha
Factorial 4 => 24
1
2
3
name -> Agnibha
age -> 26
Country -> India
2
4
6
A
[5, 6]
> 5 : true
> 1 : false
Double : [2, 4, 6, 8, 10, 12]
```

That is all for this article. Though we have just touched the tip of the iceberg as there are a lot of things that can be done by groovy. This article was just there to get you going with the language.

For more on Groovy you can just visit their official documentation because that is very rich and adequate for learning. The code samples will also be available at Github.

## LINKS:

- Docs: <https://dgit.in/GroovyDocs>.
- Github: <https://dgit.in/Groovy101Git>. 

## \*VIDEOS



### \*The Complete Apache Groovy Developer Course

The entire course from Dan Vega, available for free on YouTube in a convenient playlist.

<https://dgit.in/GroovyCom>



### \*What's New in Xcode 10: WWDC 2018

iOS Engineer and YouTuber Sean Allen discusses what new in Xcode 10 based on the Platforms State of the Union session at WWDC 2018.

<https://dgit.in/XCodeWhatsNew>



### \*ARKit 2 Tutorial

Learn how to scan real world objects to detect them in your app with ARKit and create a stunning AR shopping experience.

<https://dgit.in/ARKit2Tut>