



Reprogrammable braille

Harvard researchers have developed materials with mechanical memory to make smaller braille books. <https://dgit.in/sep18-50-1>



Boeing helicopters for India

Boeing has finished testing the first batch of Apache and Chinook helicopters for the Indian Air Force. <https://dgit.in/sep18-50-2>

```
HOW IZ [object] [function
name] (YR [argument1] (AN YR
[argument2] (AN YR [argument3]
...)))
```

```
[function code]
```

```
IF U SAY SO
```

A function inside a BUKKIT can access variables and other functions of the BUKKIT by using ME'Z [var] or ME IZ [function name] (YR [argument1] (AN YR [argument2] (AN YR [argument3] ...))) MKAY.

```
HAI 1.2
```

```
I HAS A DABBA ITZ A BUKKIT
```

```
BTW DECLARING AN ARRAY
```

```
DABBA HAS A DOGGO ITZ "DOGE"
```

```
BTW DOGGO IS A STRING VARIABLE
```

```
THAT IS INSERTED INTO ARRAY
```

```
DABBA
```

```
VISIBLE DABBA'Z DOGGO
```

```
KTHXBYE
```

The output when you run the code given above will be **DOGE**.

CHANGING TYPES

To convert a value of one type to another type, we use type casting. For example casting a NUMBAR to a NUMBR truncates the decimal portion of the floating point number.

```
HAI 1.2
```

```
I HAS A pie ITZ "3.14"
```

```
VISIBLE pie
```

```
BTW this is type casting
```

```
MAEK pie A NUMBAR
```

```
VISIBLE pie
```

```
KTHXBYE
```

IF-THEN STATEMENT

The if-then statement works the same way as in other languages. It evaluates a simple boolean (TROOF) and then executes lines conditionally. The if-then statements here have four keywords:

O RLY?, **YA RLY**, **NO WAI** and **OIC**. The general syntax of a if-then block is:

```
<any_expression>
```

```
O RLY?
```

```
YA RLY
```

```
<code to execute if above condition is true>
```

```
NO WAI
```

```
<code to execute in this block>
```

```
OIC
```

While using the if-then statements, an optional MEBBE <any expression> may be used between the YA RLY and NO WAI blocks. If the <any expression> following MEBBE is True (WIN), then that block is executed. Otherwise, if that expression is false (FAIL), the block is skipped until the next MEBBE, NO WAI, or OIC statements.

```
BOTH SAEM PET AN "Dog"
```

```
O RLY?
```

```
YA RLY, VISIBLE "Your dog is shooo cutezzz"
```

```
MEBBE BOTH SAEM BREED AN "Beagle"
```

```
VISIBLE "I luv beagles!"
```

```
OIC
```

CASE STATEMENTS

For lolcode, The keyword 'WTF?' is the equivalent to switch in many other languages. The keyword WTF? takes IT as the expression value for comparison. To use WTF, a case block is started by OMG which can only be a literal. All OMG blocks must be terminated by a GTFO (break) statement.



If an OMG block is not terminated by a GTFO, then the next OMG block is executed till GTFO is reached. If none of the literals evaluate as true, then default case is signified by OMG-WTF as shown below.

```
WTF?
```

```
OMG <any value to compare>
```

```
<code block to execute
```

```
if expression is satisfied>
```

```
OMG <any value to compare>
```

```
<code block to execute
```

*POINTERS



*Learn Lolcode

A full fledged tutorial on Lolcode that takes you through everything in this article in greater detail along with exception handling, additional resources and more.

<https://dgit.in/LearnLol>



*Learn ArnoldC

ArnoldC is an imperative programming language where the basic keywords are replaced with quotes from different Schwarzenegger movies.

<https://dgit.in/ArnoldC>



*The Shakespeare Programming Language

A programming language created with the design goal to make the source code resemble Shakespeare plays. The characters in the play are variables.

<https://dgit.in/ShakespeareLang>