



YouTube Music adds new feature

YouTube Music added a 'Released' playlist which has the hottest 50 songs much like Spotify and Apple Music. <https://dgit.in/sep19-82>



US and France strike a deal

The US and France government have reached a deal that ends the feud over France's digital taxes on tech giants. <https://dgit.in/sep19-83>

named `pubspec.yaml` will also be generated. Since you've used a stagehand template, your `pubspec.yaml` file will contain certain dependencies which need to be obtained. To do so, type:

```
pub get
```

You should now check if everything is in order. By default, these templates are built to echo a hello world statement. Run the app by typing:

```
dart bin/main.dart
```

You should get the following output:

```
Hello world: 42!
```

Now you can move onto building your app by adding all the functionalities in the `cli.dart` file. After all that is done, compiling is as easy as specifying which manner you want to compile. For AOT compile, you would want to type the following:

```
dart2aot bin/main.dart bin/main.dart.aot
```

And for runtime compiling, use:

```
dartaotruntime bin/main.dart.aot
```

Runtime is way faster and helps with making quick changes in your code. You can easily perform an AOT compile when you're heading into production, though runtime works just as fine.

LANGUAGE SAMPLES

You'll obviously need to understand some of the libraries and syntax used in Dart, so let's go over the ones you'll use the most.

Variables

Dart doesn't require you to explicitly state the type of the variable. Based on whatever you're passing onto the variable, it will handle the initiation and the type on its own. Example:

```
var name = 'Voyager I';
var year = 1977;
var antennaDiameter = 3.7;
var flybyObjects = ['Jupiter',
  'Saturn', 'Uranus', 'Neptune'];
var image = {
  'tags': ['saturn'],
  'url': '//path/to/saturn.jpg'
};
```

Functions

Functions are written practically in the same manner as you would with either C or C++.

Ideally, you want to be specifying the types of each of the arguments that will be passed onto the function along with the return value.

```
int fibonacci(int n) {
  if (n == 0 || n == 1) return n;
  return fibonacci(n - 1) + fibonacci(n - 2);
}
```

```
var result = fibonacci(20);
```

Inheritance

You can extend classes in Dart in much the same manner as in Java.

```
class Orbiter extends Spacecraft {
  num altitude;
  Orbiter(String name, DateTime launchDate, this.altitude)
    : super(name, launchDate);
}
```

Async

Practically a boon for folks working in a client-server environment. Asynchronous calls are the way to go. In Dart, you can use `async` and `await` to get the job done.


```
const oneSecond = Duration(seconds: 1);
// ...
Future<void>
```

*CODING MATTERS



*Dart in 2 hours

Learn all the basics of Dart in under 2 hours with this simple tutorial video. <https://dgit.in/2zp5FaY>



*Flutter + Dart

Make the most of Dart with Flutter. Here are some example apps to check out the various functionalities of dart. <https://dgit.in/2U3l22v>



*Dart 2 migration guide

There are barely any differences between the two versions. Figure out how to migrate your Dart 1 code to Dart 2 with this guide. <https://dgit.in/324kY57>